FURTABLE VACUUM UNIT



EVACE 3200 SPECIFICATIONS



SEPTIC TANKS



GREASE TRAPS



AND MUCH MORE!

Vacuum System

- Yanmar 10 HP diesel engine with electric start motor
- 115 CFM Conde rotary vane vacuum pump
- · Belt driven with guard
- · 12 V battery
- 50mm vacuum system
- All plumbing uses steel reinforced fuel suction hose with stainless steel clamps
- 75mm vacuum tank inlet including blockage removal port with camlock fitting
- 100mm discharge ball valve
- 10m of 50mm suction hose including ball valve and suction lance
- · Primary shut off
- · Secondary shut off with drain point
- Oil catch muffler with stainless steel filter and drain point

Vacuum Tank

- 3200 L waste capacity
- 5mm stainless steel barrel construction, skid mounted designed to be forked from two sides
- Tie down points
- Vacuum tank constructed to withstand 65 percent vacuum, no pressure capability
- 250mm wash out facilities, 2 eyebolts and wing nuts to secure lids
- 1350 KG empty weight
- · Sight glasses to observe waste level in tank
- Dimensions: 4420mm L, 1370mm W, 1880mm H

Other Components

- 1200 L water capacity with sight tube
- 12 V water pump 17 LPM flow 40 PSI pressure, manual on/off switch and water filter
- 18mm garden hose, 15m with spray nozzle
- Pressure relief valve
- · Vacuum relief valve
- 65mm vacuum pressure gauge

ALSO AVAILABLE EVAC 800 AND EVAC 1600